



Please Note

The meter is intended to be installed in a Mechanical Environment 'M1', with Shock and Vibrations of low significance, as per 2004/22/EC Directive. The meter is intended to be installed in Electromagnetic Environment 'E2', as per 2004/22/EC Directive.

ş

Installation of this device may only be performed by qualified personnel.

Technical support

In case you have any questions about our product, please contact Rayleigh Instruments on 01245 428500.

Attention

The Meter housing is sealed. Warranty is void if the seal is broken or removed



RAYLEIGH INSTRUMENTS LIMITED Cutlers Road South Woodham Ferrers Chelmsford Essex CM3 5WA UK







Single Phase Energy Meter – 100A Direct MID With Communications / Pulsed Output


DECLARATION OF CONFORMITY According to Directive 2004/22/EC Report Ref: SHES1203000458MI Issued 15 th August 2012 Issued 15 th August 2012 Compiled by: SGS Product RI-78-80-C Rating R04 Output R5485/SO. Pulse The test sample has been tested in accordance with the requirements of Directive 2004/22/EC as stated on Certificate 0120/SGS0138	S i	Rayleigh Instruments Limited
Report Ref: SHES1203000458MI Issued 15 th August 2012 Compiled by: SGS Product : Single Phase Energy Meter Model No. : R1-78-80-C Rating : Notput : R5485/SO. Pulse The test sample has been tested in accordance with the requirements of Directive 2004/22/EC as stated on Certificate 0120/SGS0138		DECLARATION OF CONFORMITY
Issued 15 th August 2012Compiled by: SGSProduct:Single Phase Energy MeterModel No.:Rating:80AOutput:R5485/SO. PulseThe test sample has been tested in accordance with the requirements ofDirective 2004/22/EC as stated on Certificate 0120/SGS0138		According to Directive 2004/22/EC
Compiled by: SGSProduct:Single Phase Energy MeterModel No. :RI-78-80-CRating:80AOutput:RS485/SO. PulseThe test sample has been tested in accordance with the requirements ofDirective 2004/22/EC as stated on Certificate 0120/SGS0138		Report Ref: SHES1203000458MI
Product:Single Phase Energy MeterModel No.:RI-78-80-CRating:80AOutput:RS485/SO. PulseThe test sample has been tested in accordance with the requirements ofDirective 2004/22/EC as stated on Certificate 0120/SGS0138		Issued 15 th August 2012
Model No. : RI-78-80-C Rating : 80A Output : RS485/SO. Pulse The test sample has been tested in accordance with the requirements of Directive 2004/22/EC as stated on Certificate 0120/SGS0138		Compiled by: SGS
Model No. : RI-78-80-C Rating : 80A Output : RS485/SO. Pulse The test sample has been tested in accordance with the requirements of Directive 2004/22/EC as stated on Certificate 0120/SGS0138		
Rating : 80A Output : RS485/SO. Pulse The test sample has been tested in accordance with the requirements of Directive 2004/22/EC as stated on Certificate 0120/SGS0138	Product :	Single Phase Energy Meter
Output : RS485/SO. Pulse The test sample has been tested in accordance with the requirements of Directive 2004/22/EC as stated on Certificate 0120/SGS0138	Model No. :	RI-78-80-C
The test sample has been tested in accordance with the requirements of Directive 2004/22/EC as stated on Certificate 0120/SGS0138	Rating :	80A
Directive 2004/22/EC as stated on Certificate 0120/SGS0138	Output :	RS485/SO. Pulse
The technical documentation required to demonstrate that the products meet the requirements of the above EU directives has been compiled and is available for inspection by relevant enforcement authorities.	above EU directives ha	tation required to demonstrate that the products meet the requirements of the s been compiled and is available for inspection by relevant enforcement

CE

Approved by/Date

Rayleigh Instruments Limited Raytel House, Cutlers Road, South Woodham Ferrers, Essex, CM3 5WA Tel. 01245428500 Fax 01245428559 Web. www.rayleigh.co.uk

5 (80)A
230V ± 20%
1600 Impulse / KWh
В
D
50Hz ± 10%
5+2 = 99999. 99 KWh LCD
-25°C to 55°C
75% Average / Short time value 95%
EN50470-1 / EN50470-3
≤1W
RS485—Modbus RTU
1600 lmp/kWh RL = 0.625 Wh/Imp RA = 0.625 Wh/Imp S0-Standard DIN 43864
52mS
0.05-0.25KHz
50mm ²



1 Live In	2 Live Out	
3 Neutral In	4 Neutral Out	
5 Pulse -	6 Pulse +	
7 B / -	8 A / +	